



REAR-PROJECTION SCREEN—GREY

RETROGRAPHIQUE GREY

» PVC **cyclorama** screen in **grey** specially for **rear-projection** and offering **excellent contrast**



CHARACTERISTICS

Name	Rear-Projection Screen—Grey	Ref	2202
Previous product name (<i>Teviloj</i>)	Retrographique Grey		
Width	± 230 cm	Weight	± 450 g/m ²
Flame-retardant rating	 M1,  Pass	Composition	100% PVC


- » **PVC cyclorama screen in grey specially for rear-projection and offering excellent contrast**
- » **Flexible PVC front-projection screen in mid-grey colour**
- » Quality projection in **High-Definition** with **excellent contrast** over a **very wide angle of vision**
- » Grey colour **greatly reduces hotspots**
- » **Optimum optical properties** (super-stable gain) thanks to the uniformity of the surface
- » HF assembly in our workshops for **outside screens** with virtually **invisible seams** (extra-fine and ultra-flat welds)
- » Excellent **light diffusion** allow use for **cycloramas**
- » Perfect for all kinds of **stages** including **theatres, operas**, etc.
- » Suitable for mounting on **frames**, as well as **motorised rollers**, and for creating **hanging screens**, etc.
- » Intrinsically **M1 flame-retardant** (length of rating not limited)
- » **Washable** and suitable for **outdoor use**
- » Sound insulation **properties**
- » Printable **material** ideal for the most adventurous scenery and productions

COLOUR



Grey
100

GAIN



ADDITIONAL INFORMATION

Thickness	± 0.3 mm
------------------	----------

ADDITIONAL INFORMATION

Appearance	Flexible screen material in grey colour with 2 different finishes front and rear: <ul style="list-style-type: none">» 1 matte textured side with grained finish» 1 more glossy side with a smooth finish
Supplied in	Rolled full-width
Average bolt length	± 100 m
Cut-to-length	Yes (minimum 5 linear metres)
Care	Wash with soapy water, rinse with fresh water. Do not use harsh abrasive detergents For all cleaning products, we recommend cleaning a test sample before washing the entire screen
Storage	We recommend: <ul style="list-style-type: none">» Store rolled wherever possible» Once screen has been made up for use, can be stored folded, but avoid creasing and never compress. (try to copy as closely as possible the initial packaging as produced in the workshop)» Store indoors (away from light and humidity)» Store at room temperature (+/- 23°C) Storage should not exceed 6 months between use.
Directions for use	<ul style="list-style-type: none">» Can be made up to any dimensions and with all finishing options (eyelets or rivets, tabs, sleeves and hems, velcro, etc.) in our workshops» Can be tensioned by stapling» If required, material can be cut on site using a craft knife (Stanley knife) or scissors (no risk of fraying)» For optimum image quality, position matte grained side towards audience» To achieve optimum flatness, we recommend storing the product in a warm place (+/-23°C) for 24 hrs prior to assembly» Suitable for outdoor and indoor use
Recommended use	<ul style="list-style-type: none">» Cycloramas» Hanging screens (theatres, opera, etc.)» Tensioned screens (events: exhibitions, conferences, etc.)» Screens mounted on motorised rollers, etc.
Accessories	<ul style="list-style-type: none">» Weighting poles» Mounting accessories (clips, tensioners, bungee cords, tabs, etc.)
Printing	Printable surface depending on type of machine and ink We recommend test-printing on samples before full-scale production Looking for an easily printable PVC material? We recommend you take a look at our range of PRINTABLE PVC
HF weldability	Excellent high-frequency welding
Elongation at break <small>Standard ISO 527-3</small>	Machine direction: > 200% Transverse direction: > 200%
Tensile strength <small>Standard ISO 527-3</small>	Machine direction: > 12 MPa Transverse direction: > 12 MPa

CONTACT OUR EXPORT TEAM

+33 (0)6 23 21 50 28



export@azur-scenic.com

The information in this document provides generic values that describe only the standard technical specifications and chemical composition of the products concerned. No guarantee is offered. Any images are non-contractual. The names of the colours are given for information purposes only and do not guarantee a specific colour.