



000



The more affordable, non-flame-retardant rated version of Cristal.

A **flexible film** in **transparent PVC** with subtle blue reflections and available in different thicknesses (0.3 mm standard, and 0.5 to 1 mm to order).

We make this tarpaulin product in our own workshops to allow even the most oversize projects, with a range of options for assembly and finishes, using **HF welding** technology.

This incredibly **hard-wearing** tarpaulin is **waterproof**, and **UV-resistant treated** making it **easy-care** and suitable for **outdoor** use.

It also has **sound insulation** properties.

This PVC film is suitable for a range of uses such as making tents and big tops, and more...

Dare to go off-piste! Control the transparency of the crystal and let your creativity speak by using it as an innovative **surface for front-projection** or **rear-projection** that's both original and **inconspicuous**!

Technical data	Value	
Reference	2503 - Cristal 30/100 not flame-retardant rated	
Width	140 cm	
Weight	370 g/m <sup>2</sup>	Other grammages available to order from 620 to 1240 g/m <sup>2</sup>
Thickness	0.3 mm	Other thicknesses available to order from 0.5 to 1 mm
Flame-retardant rating	N/A	For the M2 flame-retardant rated version, please ask your sales team member about our other Cristal products
Supplied in	Roll of 65 m Rolled full width ± 34 kg/pce	Cut-to-length possible for standard 30/100ths thickness Available in whole length only for other weights (meterage of lengths varies according to thickness)
Flexibility (grade)	3S	
Tear-resistance	Width: 21.2 N Length: 19.8 N	Standard: ASTM D1004-13
Breaking strain	Width: 25.6 MPa Length: 29.3 MPa	Standards: ISO 527-1 and 527-3
Elongation at break	Width: 350% Length: 320%	Standards: ISO 527-1 and 527-3
Low-temperature resistance	-40°C	Standard: ASTM D746
Shrinkage (80°C - 10 min)	Width: 0.7% Length: 2.2%	Standard: DIN 53377

## Additional information

Composition	100% PVC
UV stability	Yes
Care	Wash with soapy water, rinse with fresh water Do not use harsh abrasive detergents We recommend testing cleaning products on a small area before cleaning the entire surface
Storage recommendations	Store rolled, indoors at room temperature. If stored folded (once manufactured), do not compress.
Cutting recommendations	Cold-cut with scissors (low risk of fraying)
High-frequency (HF) welding	Good HF weldability. We make screens of all dimensions and finishes in our own workshops.
Appearance	Flexible, transparent gloss PVC tarpaulin with faint blue highlights
Recommended use	Making marquees, tents and big tops, etc. Outdoor use
Accessories	Tensioners, clips, bungee cords, etc.



## CONTACT OUR EXPORT TEAM

+33 (0)6 23 21 50 28



[export@azur-scenic.com](mailto:export@azur-scenic.com)

The information in this document provides generic values that describe only the standard technical specifications and chemical composition of the products concerned. No guarantee is offered. Any images are non-contractual. The names of the colours are given for information purposes only and do not guarantee a specific colour.