


Ref: 2504 - 2505 - 2508



A **flexible film** in **transparent PVC** with subtle blue reflections, **M2 rated** and available in 3 different thicknesses (0.3 to 0.8 mm).

We make this tarpaulin product in our own workshops to allow even the most oversize projects, with a range of options for assembly and finishes, using **HF welding** technology.

This incredibly **hard-wearing** tarpaulin is **waterproof**, and **UV-resistant treated** and **easy-care**, making it suitable for use both indoors and **outdoors**.

It also has **sound insulation** properties. This PVC film is suitable for a range of uses such as making tents and big tops, making stage sets, and more...







Dare to go off-piste! Control the transparency of the crystal and let your creativity speak by using it as an innovative **surface for front-projection** or **rear-projection** that's both **original** and **inconspicuous**!

Colour



Transparent  
ooo

Characteristics

Name	Cristal 30/100 <sup>ths</sup>	Cristal 50/100 <sup>ths</sup>	Cristal 80/100 <sup>ths</sup>
Reference	2504	2505	2508
Width	± 140 cm	± 140 cm	± 140 cm
Weight	± 390 g/m <sup>2</sup>	± 650 g/m <sup>2</sup>	± 1040 g/m <sup>2</sup>
Thickness	± 0.3 mm	± 0.5 mm	± 0.8 mm
Flame-retardant rating	 M2,  B1	 M2,  B1	 M2,  B1

# Characteristics

Name	Cristal 30/100 <sup>ths</sup>	Cristal 50/100 <sup>ths</sup>	Cristal 80/100 <sup>ths</sup>
Composition	100% PVC	100% PVC	100% PVC
Length and weight of whole roll	± 65 m (± 36 kg ea.)	± 40 m (± 36 kg ea.)	± 25 m (± 36 kg ea.)
Supplied in	Rolled full-width	Rolled full-width	Rolled full-width
Cut-to-length	Yes (minimum 5 linear metres)	No	No
Flexibility (grade)	3S	3S	3S
Tear-resistance	Width: 19.3 N Length: 17.2 N	Width: 31.3 N Length: 29.1 N	Width: 52.4 N Length: 51.5 N
Breaking strain	Width: 23.2 MPa Length: 28.7 MPa	Width: 21.0 MPa Length: 22.4 MPa	Width: 21.6 MPa Length: 23.4 MPa
Elongation at break	Width: 340% Length: 310%	Width: 350% Length: 300%	Width: 350% Length: 300%
Low-temperature resistance T°	-25°C	-10°C	-8°C
Shrinkage	Width: 0.9% Length: 2.7%	Width: 0.9% Length: 3.2%	Width: 19% Length: 3.1%
UV stability	Yes	Yes	Yes

# Additional information

Appearance	Flexible, transparent PVC tarpaulin with faint blue highlights Identical appearance on both sides
Care	Wash with soapy water, rinse with fresh water. Do not use harsh abrasive detergents. We recommend testing cleaning products on a small area before cleaning the entire surface.
Storage recommendations	Store rolled, indoors at room temperature. If stored folded (once manufactured), do not compress.
Cutting recommendations	Cold-cut with scissors (low risk of fraying)
Directions for use	Good HF weldability. We make screens of all dimensions and finishes in our own workshops.
Recommended use	Making marquees, tents and big tops, decorative and interior-design elements etc. Indoor and outdoor use
Accessories	Tensioners, clips, bungee cords, etc.

## CONTACT OUR EXPORT TEAM

+33 (0)6 23 21 50 28



[export@azur-scenic.com](mailto:export@azur-scenic.com)

The information in this document provides generic values that describe only the standard technical specifications and chemical composition of the products concerned. No guarantee is offered. Any images are non-contractual. The names of the colours are given for information purposes only and do not guarantee a specific colour.