

Ref : 6402



An elegant **sun shade** material with **acoustic** properties rated **M1** flame-retardant and available in an incredible range of **24 colours**.

























Washable FR polyester material that's ideal for both **indoor** and **outdoor** use.

It can be used for making **curtains**, as well as **wall hangings**, roman blinds, and even Japanese screens.









Certified with the **Oeko Tex** label, this fabric is **environmentally friendly**.



Colours

							
Black 003	Cream 030	Light grey 110	Pearl 120	Grey blue 135	Steel 170	Coral 330	Mandarin 350
							
Canary yellow 422	Lemon 450	Beige 500	Light beige 501	Linen 513	Moka 570	Grey-green 640	Spinach 670
							
Azure 730	Royal 760	Denim blue 782	Petrol 784	Navy 790	Fig 825	Pale pink 904	Old rose 905

Characteristics

Name	Chausey Canvas			
Reference	6402			
Roll length	50 m (delivered in 2 x 25 m)			
Width	280 cm			
Cut-to-length	Yes			
Weight	270 g/m ²			
Thickness	0.5 mm			
Composition	100% FR Polyester			
Flame-retardant rating	 M1  B1  UNO		Standard: NF P 92-503-504-505 Standard: DIN 4102 Standard: UNI 8456 / UNI 9174	
Thermal and visual performance	Light colours gt: 36% fc: 61%	Mid-tone colours gt: 41% fc: 69%	Standard: DIN EN 13363 Standard: DIN EN 14501	
Acoustic	Noise reduction coefficient (NRC): 0.41			Standard: ISO 354
Resistance Light fastness Units class /8	Light colours 6	Mid-tone colours 5 - 6	Dark colours 3 - 4	Standards ISO 105 B02
Care	    			
Recommended applications	Japanese screens Mattress cover Curtains Pillow Wall hanging Roman blinds			

Average noise reduction coefficient (NRC) in alpha Sabin

The NRC obtained gives a material's ability to allow the passage of sound waves. An NRC of near 0 is given to materials that allow the passage of sound waves or which cause little disruption to noise. These are therefore recommended, for example, for covering an acoustic panel. Conversely, a rating of close to 1 means an absorbent material or which strongly disrupts through the reflection of sound waves. It is therefore highly recommended, for example, for improving the acoustic performance of a space according to the required specifications.

CONTACT OUR EXPORT TEAM

+33 (0)6 23 21 50 28



export@azur-scenic.com